



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:
 Pitch : 5.08mm
 Rated Voltage : 300V
 Rated Current : 10A
 Withstand Voltage :
 AC2500V for 1 minute
 Insulation Resistance :
 500MΩ / DC500V
 Using Temperature Range :
 -40℃ ~ +105℃
 Wire range : 26~ 12AWG

技术要求:
 间距: 5.08mm
 额定电压: 300V
 额定电流: 10A
 耐电压值: AC2500V/min
 绝缘阻抗: 500MΩ/DC500V
 使用条件: -40℃~+105℃
 适用线规: 26~12AWG

6	LZ1-耳朵螺母	SM00B25000V	2	黄铜			
5	LC60-5.08五金件	2083B0001AV	P	磷青铜	镀锡		
4	LC6-5.08-弹片	F2A0DLC658BV	P	不锈钢			
3	LC6-5.08-按钮	1020D0Y01AV	P	PA66			
2	LC60-5.08-盖板	2083COYXXAV	1	PA66			
1	LC60MG-5.08-本体	2083NOYXXAV	1	PA66			
NO.	NAME OF PART	NO. OF PART	Q' TY	MATERIAL	NOTES		
DES.	ZD	DATE	2020/07/23	UNITS	MM	THIRD ANGLE PROJECTION	SHEET
CHK.		DATE		SIZE	A4		1 of 1
APP.		DATE		SCALE	1:1	DWG NO.	REV: V0
上海有乐电气有限公司 Shanghai YouLe Electric C O., LTD						TITLE	LC60MG-5.08-XXP-1Y-00A
							LC60MG-5.08-成品

	pitch dimension			Nominal dimension					— /
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10